

SERIES 7290.0010 SANOLEGNO SATIN PARQUET – WATER BASED PAINT
Uses

Transparent satin water based varnish for the finishing of parquet, skirting, board frame etc.
 It is used to preserve, to decorate and to make water-repellent the wood.

General data

Protective paint for wood. It is a opalescent liquid.

It enlivens wood vein and improve its appearance with an softly satin effect.

Furthermore the product has the following characteristics:

- quick drying
- high elasticity
- high resistance to the abrasion (scratches)
- resistance to the water
- good resistance to the chemical agents

Technical data (data gathered at the temperature of 20°C)

Viscosity Ford Cup n° 4	Sec.	100 ± 5
Specific gravity	kg/l	1,020 ± 0,030
Solids	%	32 ± 2
Theoretical spreading rate	mq/l	10 ± 2
Appearance of the film	gloss	25 ± 5 (setinato)
Thinner	Code	Water
Dust free	Minutes	5-7
Touch free	Hours	1,5
Dry in depth	Hours	12
Over coatability	Hours	4 – 6

Methods of application

By brush, by roll, by spraygun	To dilute with	Water at 5-7%
Spray gun	Nozzle size Pressure	mm 1,2 - 1,4 Atm 3 - 5
Airless	Nozzle size Pressure Compression ratio	0,013 - 0,015 inches 120 - 140 kg/cm ² 30 ÷ 1

Recommended painting cycles

It could be applied on 7280.0600, on polyurethane or nitro primers, carefully sanded, or directly on raw wood applying one first coat more diluted (10 – 15%). After 12 – 18 hours make a light sanding with sandpaper 220 / 240 and to finish with a second coat of 7290.0010 Sanolegno satin parquet.

Notes

- Keep far from children.
- It fears frost.
- The product must be stocked at temperature higher than +5°C. The product can't be applied below the temperature of +8/10°C.
- Wash tools with water right after use. The hardened product can be removed from the tools with Nitro Thinner 9210.0012.
- Shake before its use.

26/06/2012